

SAFETY DATA SHEET

M5420 NA_EN



SODIUM METASILICATE ANHYDROUS

MSDS No.: M5420

Rev. Date: 08-05-2026

Rev. Num. 06

1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Company Identification:	Cooper Natural Resources Inc. 7755 Bellaire Drive South Ft Worth, Texas 76132 (817) 244-9700
24 Hour Emergency Telephone Number:	1-800-733-3665 or 1-972-404-3228 (U.S.); CHEMTREC (U.S.): 1-800-424-9300; CHEMTREC (outside U.S.): +1 703-527-3887
To Request an SOS:	MSDS@oxy.com or 1-972-404-3245
Customer Service:	1-800-752-5151 or 1-972-404-3700
Trade Name:	Special Grade S-25; Sodium Metasilicate Anhydrous Fines
Synonyms:	Anhydrous Metasilicate, Sodium Metasilicate Anhydrous
Product Use:	Cleaner, Detergents / Soaps

2. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW:

Color:	White
Physical State:	Solid
Appearance:	Granular
Odor:	Odorless
Signal Word:	DANGER

MAJOR HEALTH HAZARDS: CORROSIVE TO RESPIRATORY TRACT, EYES, SKIN AND DIGESTIVE TRACT. MAY CAUSE PERMANENT EYE DAMAGE. HARMFUL IF SWALLOWED.

PHYSICAL HAZARDS: MAY BE CORROSIVE TO METALS.

PRECAUTIONARY STATEMENTS: Keep only in original container. Wear protective gloves, protective clothing, eye, and face protection. Do not breathe dust. Wash thoroughly after handling. Do not eat, drink or smoke when using this product.

M5420 NA EN

Rev. Num. 06

*****k'k'l/-k* /r/r*****'r/l** /r/l*/r/r***** /r/r*****trd/rd***** /rd*****

Inhalation: Inhalation of dusts may cause irritation of the upper respiratory tract with sore throat, coughing and shortness of breath. Upon contact with moist mucous membranes, sodium metasilicate is highly alkaline and may cause corrosive damage. May cause severe irritation of the respiratory tract with coughing, choking, pain and possibly burns of the mucous membranes. In some cases, pulmonary edema and/or pneumonia may develop, either immediately or more often within 72 hours. The symptoms may include tightness in the chest, dyspnea, frothy sputum, cyanosis, and dizziness. Physical findings may include moist rales, low blood pressure and high pulse pressure.

Eye contact: Dust or mist may cause severe irritation, pain and corneal burns (possibly leading to blindness). The full extent of the injury may not be immediately apparent.

Ingestion: May cause immediate pain and severe burns of the esophagus and gastrointestinal tract with vomiting, nausea, and diarrhea. Edema of the epiglottis and shock may occur.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Component	%	CAS Number
Sodium Metasilicate	95 - 99.5	6834-92-0

4. FIRST AID MEASURES

INHALATION: If adverse effects occur, remove to uncontaminated area. Give artificial respiration if not breathing: If breathing is difficult, oxygen should be administered by qualified personnel. If respiration or pulse has stopped, have a trained person administer Basic Life Support (Cardio-Pulmonary Resuscitation and/or Automatic External Defibrillator) and **CALL FOR EMERGENCY SERVICES IMMEDIATELY.**

SKIN CONTACT: Immediately flush contaminated areas with water. Remove contaminated clothing, jewelry, and shoes immediately. Wash contaminated areas with soap and water. Thoroughly clean and dry contaminated clothing and shoes before reuse. **GET MEDICAL ATTENTION IMMEDIATELY.**

EYE CONTACT: Immediately flush eyes with a directed stream of water for at least 15 minutes, forcibly holding eyelids apart to ensure complete irrigation of all eye and lid tissues. Washing eyes within several seconds is essential to achieve maximum effectiveness. GET MEDICAL ATTENTION IMMEDIATELY.

INGESTION: Never give anything by mouth to an unconscious or convulsive person. If swallowed, do not induce vomiting. Give large amounts of water. If vomiting occurs spontaneously, keep airway clear. Give more water when vomiting stops. GET MEDICAL ATTENTION IMMEDIATELY.

Notes to Physician: The absence of visible signs or symptoms of burns does NOT reliably exclude the presence of actual tissue damage.

SODIUM METASILICATE ANHYDROUS

M5420 NA_EN

MSDS No.: M5420

Rev. Date: 08-05-2026

Rev. Num. 06

5. FIRE-FIGHTING MEASURES

Fire Hazard: Negligible fire hazard.

Extinguishing Media: Use media appropriate for surrounding fire.

Fire Fighting: Move container from fire area if it can be done without risk. Avoid inhalation of material or combustion by-products. Stay upwind and keep out of low areas.

Sensitivity to Mechanical Impact: Not sensitive.

Sensitivity to Static Discharge: Not sensitive.

Flash point: Not flammable

6. ACCIDENTAL RELEASE MEASURES

Occupational Release: Shovel dry material into suitable container. Wear appropriate personal protective equipment recommended in Section 8 of the SOS. Flush spill area with water, if appropriate. Liquid material may be removed with a vacuum truck. Wet material is slippery under foot. Keep out of water supplies and sewers. This material is alkaline and may raise the pH of surface waters with low buffering capacity. Releases should be reported, if required, to appropriate agencies.

7. HANDLING AND STORAGE

Storage Conditions: Store and handle in accordance with all current regulations and standards. Keep container tightly closed and properly labeled. Do not store in aluminum container or use aluminum fittings or transfer lines, as flammable hydrogen gas may be generated. Keep separated from incompatible substances.

Handling Procedures: Avoid creation of dust. Avoid breathing dust. Do not get in eyes, on skin, or on clothing. Wash thoroughly after handling.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Regulatory Exposure Limit(s): None

Non-Regulatory Exposure Limit(s): As listed below

OXYREL
8 hr TWA

Recommended Exposure Limit: 3 mg/m³ ceiling (internal Occupation Exposure Limit based on data from analogous chemicals)

ENGINEERING CONTROLS: Provide local exhaust ventilation where dust or mist may be generated. Ensure compliance with applicable exposure limits.

SODIUM METASILICATE ANHYDROUS

M5420 NA_EN

MSDS No.: M5420

Rev. Date: 08-05-2026

Rev. Num. 06

PERSONAL PROTECTIVE EQUIPMENT:

Eye Protection: Wear safety glasses with side-shields. If eye contact is likely, wear chemical resistant safety goggles. When wet mixing, wear splash resistant safety goggles with a faceshield. Provide an emergency eye wash fountain and quick drench shower in the immediate work area.

Skin and Body Protection: Wear protective clothing to minimize skin contact. When potential for contact with wet material exists, wear Tychem® or similar chemical protective suit. When potential for contact with dry material exists, wear disposable coveralls suitable for dust exposure, such as Tyvek®.

Hand Protection: Wear appropriate chemical resistant gloves.

Protective Material Types: Butyl rubber, Natural rubber, Neoprene, Nitrite, Tychem®, Tyvek®

Respiratory Protection: A NIOSH approved respirator with high efficiency particulate air (HEPA) cartridges may be permissible under certain circumstances where airborne concentrations are expected to exceed exposure limits, or when symptoms have been observed that are indicative of overexposure. A respiratory protection program that meets 29 CFR 1910.134 must be followed whenever workplace conditions warrant use of a respirator.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical State:	Solid
Appearance:	Granular
Color:	White
Odor:	Odorless
Molecular Formula:	Na ₂ SiO ₃
Boiling Point/Range:	Not applicable
Melting Point/Range:	1990 F (1088 C)
Vapor Pressure:	Not applicable
Specific Gravity (water-1):	Not applicable
Bulk Density:	54 - 70 lbs/ft ³ (loose)
Water Solubility:	16%
pH:	12.7 (1% aqueous solution)
Volatility:	Not applicable
Flash point:	Not flammable

10. STABILITY AND REACTIVITY

Reactivity/ Stability: Stable at normal temperatures and pressures. Prolonged contact with incompatible metals may produce flammable hydrogen gas.

Conditions to Avoid: Contact with acids will cause evolution of heat. Carbon monoxide gas may form upon contact with reducing sugars, food and beverage products in enclosed spaces.

Incompatibilities/ Materials to Avoid: Acids, Prolonged contact with aluminum, brass, bronze, copper, lead, tin, zinc or other alkali sensitive metals or alloys

Hazardous Decomposition Products: None reasonably foreseeable

Hazardous Polymerization: Will not occur

SODIUM METASILICATE ANHYDROUS

M5420 NA_EN

MSDS No.: M5420

Rev. Date: 08-05-2026

Rev. Num. 06

11. TOXICOLOGICAL INFORMATION

IRRITATION DATA:

250 mg/24 hour(s) skin-human severe; 250 mg/24 hour(s) skin-rabbit severe; 250 mg/24 hour(s) skin-guinea pig moderate

TOXICITY DATA:

Component	LD50 Oral:	LC50 Inhalation:	LD50 Dermal:
Sodium Metasilicate	600 mg/kg (Rat)		

ACUTE TOXICITY:

Sodium metasilicate can produce caustic burns (i.e., colliquative necrosis) and induce hypocalcemia by binding calcium. Oral administration of sodium metasilicate to rats and mice (1153 and 770 mg/kg, respectively) produced ulceration or bleeding in the stomach, duodenum, and small intestine. Oral doses of a 20% solution (464, 1000, 2150, and 4640 mg/kg) produced gasping, dyspnea, acute depression, and/or nasal discharge at 1000 mg/kg; and the highest dose caused death. Injection of a neutralized 2.0% sodium metasilicate solution (-1200 mg/kg on day 1 and 800 mg/kg on days 2 and 3) decreased rat spleen weight by 60% and increased kidney weight. Microscopic lesions of the lymphatic tissues and cellular damage in the intestinal mucosa were also observed.

CHRONIC TOXICITY:

No data were available regarding chronic exposure, reproductive or teratological effects, or carcinogenicity for sodium metasilicate.

CARCINOGENICITY: This product is not classified as a carcinogen by NTP, IARC or OSHA.

MUTAGENIC DATA: In assays using *Bacillus subtilis* strains without metabolic activation, sodium metasilicate (0.005-0.5 M) was not genotoxic.

12. ECOLOGICAL INFORMATION

ECOTOXICITY DATA:

Aquatic Toxicity: This material has exhibited moderate toxicity to aquatic organisms.

FATE AND TRANSPORT:

BIODEGRADATION: This material is inorganic and not subject to biodegradation.

PERSISTENCE: This material is believed to persist in the environment.

BIOCONCENTRATION: This material is not expected to bioconcentrate in organisms.

ADDITIONAL ECOLOGICAL INFORMATION: This material has exhibited slight toxicity to terrestrial organisms.

SODIUM METASILICATE ANHYDROUS

M5420 NA_EN

MSDS No.: M5420

Rev. Date: 08-05-2026

Rev. Num. 06

13. DISPOSAL CONSIDERATIONS

Reuse or recycle if possible. Dispose in accordance with all applicable regulations. May be subject to disposal regulations: U.S. EPA 40 CFR 261. Hazardous Waste Number(s): D002 (Corrosive).

14. TRANSPORT INFORMATION

U.S. DOT 49 CFR 172.101:

UN NUMBER: UN3262
PROPER SHIPPING NAME: Corrosive solid, basic, inorganic, n.o.s. (SODIUM METASILICATE)
HAZARD CLASS/ DIVISION: 8
PACKING GROUP: II
LABELING 8
REQUIREMENTS:

CANADIAN TRANSPORTATION OF DANGEROUS GOODS:

UN NUMBER: UN3262
SHIPPING NAME: Corrosive liquid, basic, inorganic, n.o.s. (SODIUM METASILICATE)
CLASS OR DIVISION: 8
PACKING/RISK GROUP: II

15. REGULATORY INFORMATION

U.S. REGULATIONS

- **OSHA REGULATORY STATUS:**

This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200)

- **CERCLA SECTIONS 102a/103 HAZARDOUS SUBSTANCES (40 CFR 302.4):** Not regulated.

- **EPCRA EXTREMELY HAZARDOUS SUBSTANCES (40 CFR 355.30):**

Not regulated

- **EPCRA SECTIONS 311/312 HAZARD CATEGORIES (40 CFR 370.10):**

Acute Health Hazard

- **EPCRA SECTION 313 (40 CFR 372.65):**

Not regulated.

- **OSHA PROCESS SAFETY (PSM) (29 CFR 1910.119):** Not regulated

- **FDA:** Sodium Silicates have Generally Recognized as Safe (GRAS) status under specific FDA regulations. Refer to 21 Code of Federal Regulations (CFR) 173, 175, 176, 177, 182, and 184, which is accessible on the FDA's website. This product is not produced under all current Good Manufacturing Practices (cGMP) requirements as defined by the Food and Drug Administration (FDA).

SODIUM METASILICATE ANHYDROUS

M5420 NA_EN

MSDS No.: M5420

Rev. Date: 08-05-2026

Rev. Num. 06

NATIONAL INVENTORY STATUS

- **U.S. INVENTORY STATUS: Toxic Substance Control Act (TSCA):** All components are listed or exempt
- **TSCA 12(b):** This product is not subject to export notification
- **Canadian Chemical Inventory:** All components of this product are listed on either the DSL or the NDSL

STATE REGULATIONS

California Proposition 65: This product is not listed, but it may contain impurities/trace elements known to the State of California to cause cancer or reproductive toxicity as listed under Proposition 65 State Drinking Water and Toxic Enforcement Act. For additional information, contact OxyChem Customer Service.

Sodium Metasilicate		
California Proposition 65 Cancer WARNING:		Not Listed
California Proposition 65 CRT List - Male reproductive toxin:		Not Listed
California Proposition 65 CRT List - Female reproductive toxin:		Not Listed
Massachusetts Right to Know Hazardous Substance List		Not Listed
New Jersey Right to Know Hazardous Substance List		Not Listed
New Jersey Special Health Hazards Substance List		Not Listed
New Jersey - Environmental Hazardous Substance List		Not Listed
Pennsylvania Right to Know Hazardous Substance List		Not Listed
Pennsylvania Right to Know Soecial Hazardous Substances		Not Listed
Pennsylvania Right to Know Environmental Hazard List		Not Listed
Rhode Island Right to Know Hazardous Substance List		Not Listed

CANADIAN REGULATIONS

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the SOS contains all the information required by the Controlled Products Regulations

WHMIS Classifications of Substances:

- E - Corrosive material

16. OTHER INFORMATION

Prepared by: OxyChem Corporate HESS - Product Stewardship

HMIS: (SCALE 0-4) (Rated using National Paint & Coatings Association HMIS: Rating Instructions, 2nd Edition)

Health: 3 Flammability: 0 Reactivity: 0

NFPA 704 - Hazard Identification Ratings (SCALE 0-4)

Health: 3 Flammability: 0 Reactivity: 0

SODIUM METASILICATE ANHYDROUS

M5420 NA_EN

MSDS No.: M5420

Rev. Date: 08-05-2026

Rev. Num. 06

Reason for Revision:

- Updated 24 Hour Emergency Telephone Number: SEE SECTION 1
- Updated FDA Statement: SEE SECTION 15
- Revised California Proposition 65 Statement: SEE SECTION 15
- Revised Preparer Information: SEE SECTION 16
- Added "End of Safety Data Sheet" phrase

IMPORTANT:

The information presented herein, while not guaranteed, was prepared by technical personnel and is true and accurate to the best of our knowledge. NO WARRANTY OF MERCHANTABILITY OR OF FITNESS FOR A PARTICULAR PURPOSE, OR WARRANTY OR GUARANTY OF ANY OTHER KIND, EXPRESS OR IMPLIED, IS MADE REGARDING PERFORMANCE, SAFETY, SUITABILITY, STABILITY OR OTHERWISE. This information is not intended to be all-inclusive as to the manner and conditions of use, handling, storage, disposal and other factors that may involve other or additional legal, environmental, safety or performance considerations, and OxyChem assumes no liability whatsoever for the use of or reliance upon this information. While our technical personnel will be happy to respond to questions, safe handling and use of the product remains the responsibility of the customer. No suggestions for use are intended as, and nothing herein shall be construed as, a recommendation to infringe any existing patents or to violate any Federal, State, local or foreign laws.

OSHA Standard 29 CFR 1910.1200 requires that information be provided to employees regarding the hazards of chemicals by means of a hazard communication program including labeling, safety data sheets, training and access to written records. We request that you, and it is your legal duty to, make all information in this Safety Data Sheet available to your employees.

End of Safety Data Sheet